INTERPRETATION OF A DIPOLE-DIPOLE ELECTRICAL RESISTIVITY SURVEY, COLADO GEOTHERMAL AREA, PERSHING COUNTY, NEVADA

Claron E. Mackelprang

September, 1980

Work performed under Contract No. DE-AC07-80ID12079

MASTER

EARTH SCIENCE LABORATORY University of Utah Research Institute Salt Lake City, Utah

Prepared for U.S. Department of Energy Division of Geothermal Energy

DISTRIBUTION OF THIS DESUMENT IS UNISMITED

D/12079-11 ESL-41

DOE/ID/12079-1 ESL-4

## INTERPRETATION OF A DIPOLE-DIPOLE ELECTRICAL RESISTIVITY SURVEY, COLADO GEOTHERMAL AREA, PERSHING COUNTY, NEVADA

by

Claron E. Mackelprang

September, 1980

#### EARTH SCIENCE LABORATORY DIVISION UNIVERSITY OF UTAH RESEARCH INSTITUTE 420 Chipeta Way, Suite 120 Salt Lake City, UT 84108

PREPARED FOR DEPARTMENT OF ENERGY DIVISION OF GEOTHERMAL ENERGY UNDER CONTRACT NUMBER DE-ACO7-80ID12079

DISCLAIMER This book was prepared as an account of work sponsored by an agency of the United States Government, Neither the United States Government *nor any* agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, *trademark*, *manufacturer*, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS COCUMENT IS UNLIMITED

#### NOTICE

This report was prepared to document work sponsored by the United States Government. Neither the United States nor its agent, the United States Department of Energy, nor any Federal employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

#### NOTICE

Reference to a company or product name does not imply approval or recommendation of the product by the University of Utah Research Institute or the U.S. Department of Energy to the exclusion of others that may be suitable.

> DISCLAIMER This book was prepared as an account of work sponsored by an agency of the United States Government, Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

> > DISTRIBUTION OF THIS COCUMENT IS UNLIMATED

### TABLE OF CONTENTS

	Page	
ABSTRACT		
INTRODUCTION		
GENERAL GEOL	OGY	
ELECTRICAL R Survey Survey Li Li Li Li	ESISTIVITY SURVEY 5   Procedure 5   Results 7   ne D 7   ne A 9   ne C 11   ne B 13	
DISCUSSION .	•••••••••	
ACKNOWLEDGEM	ENTS	
REFERENCES .	••••••••••	
APPENDIX - Co	omputed Resistivity and Interpreted Sections 20	
	ILLUSTRATIONS	
Figure 1	Location Map	
Figure 2	Line D Observed Apparent Resistivity/Interpreted Section 8	
Figure 3	Line A Observed Apparent Resistivity/Interpreted Section 10	
Figure 4	Line C Observed Apparent Resistivity/Interpreted Section 12	
Figure 5	Line E Observed Apparent Resistivity/Interpreted Section 14	
Figure 6	Line B Observed Apparent Resistivity/Interpreted Section 15	
Plate I	Resistivity Survey Line Location and Geologic Base Map . in pocke	et
Plate II	Interpreted Electrical Resistivity Distribution at a Depth of 1000 Feet in pocket	et
Plate III	Interpreted Schematic of Hydrothermal Reservoir in pocke	et
Figure A1	Line D Computed Resistivity/Interpreted Section 21	

Figure A2	Line A	Computed	Resistivity/Interpreted	Section.	•	•	•	•	22
Figure A3	Line C	Computed	Resistivity/Interpreted	Section.	•	•	٠	•	23
Figure A4	Line E	Computed	Resistivity/Interpreted	Section.	•	•	•	•	24
Figure A5	Line B	Computed	Resistivity/Interpreted	Section.	•	•	•	•	25

Page

#### ABSTRACT

An electrical resistivity survey in the Colado geothermal area, Pershing County, Nevada has defined areas of low resistivity on each of five lines surveyed. Some of these areas appear to be fault controlled. Thermal fluids encountered in several drill holes support the assumption that the hot fluids may be associated with areas of low resistivity. The evidence of faulting as interpreted from modeling of the observed resistivity data is therefore particularly significant since these structures may be the conduits for the thermal fluids.

Sub-alluvial fault zones are interpreted to occur between stations 0-5 NW on Line D and on Line A between stations 4 NW and 4 SE. Fault zones are also interpreted on Line C near stations 1 NW, 1 SE, and 3 SE, and on Line E between stations 2-4 NW and near 1 SE. No faulting is evident under the alluvial cover on the southwest end of Line B.

A deep conductive zone is noted within the mountain range on two resistivity lines. There is no definite indication that thermal fluids are associated with this resistivity feature.

#### INTRODUCTION

The Colado geothermal area is located in Pershing County approximately 7 miles northeast of Lovelock, Nevada (Figure 1). The main area of geothermal exploration is along the west flank of the West Humboldt Range, lying between the railroad sidings of Kodak and Woolsey (Plate I), a distance about 4.5 miles.

The Earth Science Laboratory Division, University of Utah Research Institute (ESL/UURI) undertook an electrical resistivity survey in April, 1980 to characterize the electrical resistivity distribution of the resource area in support of the Getty Oil Company geothermal exploration effort. Their interest in the geothermal potential of the area was stimulated when, while drilling on mining claims nearby, they encountered a light flow of steam and thermal waters (Wayne Shaw, personal communication).

An earlier geophysical survey designed specifically for the evaluation of the geothermal potential in the Colado area was performed in 1977 for Getty Oil Company by Electrodyne Surveys of Sparks, Nevada. Numerous techniques (AMT-MT, TDEM, Telluric, Electrical Resistivity, Gravity and Ground Magnetic) were applied with mixed results.

A comparison of this dipole-dipole resistivity survey with the Electrodyne resistivity surveys shows the two data sets to be incompatible. The dipole-dipole data are more definitive in delinating not only areas of low apparent resistivity but structurally controlled areas as well. The data sets from the survey by Electrodyne are not supportive of each other; technique application and processing errors are involved, and Electrodyne notes discrepancies in their report.



۲

-

#### GENERAL GEOLOGY

The Colado geothermal area is indicated by hot water wells in alluvium along the west flank of the West Humboldt Range. Shallow thermal gradient holes less than 500 feet deep have encountered thermal fluids upwards of 113.5°C at a depth of 250 feet.

To gain a better understanding of the geothermal environment, Sibbett (1980) recently mapped the geology of the West Humboldt Range (Plate I) adjacent to the geothermal area. The following is taken from the abstract of his report.

The West Humboldt Range consists mainly of Triassic to Jurassic slaty shale to quartzite of the Auld Lang Syne Group. Carbonate rocks of the Lovelock Formation have been thrust over the pelitic rock on the south end of the area. Erosional remnants of Tertiary tuffs and sediments overlay the metasediments in the range.

Several thrust faults are exposed south of Coal Canyon and a structural break in the Mesozoic rocks exists under Coal Canyon. Several low-angle faults occur to the north but their effect, if any, on the geothermal occurrence is not known.

The principal structures are high-angle faults striking north-northwest, northeast and north-south. The horst-to-graben transition along the range front consists of several step faults following an irregular south-to-north trend. The structural pattern noted along the west edge of the range probably continues to the west under the Quaternary alluvium. The thermal waters are thought to rise along a major fault or fault system to the base of the alluvium.

A more detailed geologic description of the Colado geothermal area can be found in Sibbett's (1980) report.

#### ELECTRICAL RESISTIVITY SURVEY

#### Survey Procedure

The field survey was conducted by JCW, Inc. of Salt Lake City, Utah during the period April 30 to May 6, 1980. The equipment used included a Scintrex Model IPC-7 15 Kw square-wave transmitter utilizing time-domain mode current generation. The potential field was measured with a Scintrex Model IPR-10 digital time-domain receiver. When electrical noise was severe, a Scintrex Model IPR-8A receiver was used in conjunction with a Hewlett Packard 7155B strip chart recorder. Transmitting electrodes were buried aluminum foil and/or steel stakes driven into the ground. The potential differences were recorded at the surface using porcelain porous pot electrodes.

The survey (Plate I) consisted of four 1000-foot dipole-dipole 7-spreads (7 transmitting electrodes) trending generally N55°W. These are normal to existing culture (railroad tracks, water lines, power lines, etc.) and mapped faults. An effort was also made to keep transmitting electrodes at least 500 feet from the cultural features.

A fifth line was oriented N27°E and crossed a bulge in the mountain range

opposite drill holes having higher recorded temperatures. This line used 2000-foot dipoles to explore for a potential geothermal reservoir at greater depth within bedrock.

Data were acquired at n-spacings 1 through 6 on all lines whenever possible. Voltages were recorded over several transmitted cycles at each receiver site. These were averaged together before the computation of apparent resistivities. A few data points are obviously in error in spite of reasonable field precautions. High noise levels in the electrical signal may be the cause. The field data are thought, however, to be accurate to at least  $^{10\%}$  exclusive of these questionable points.

#### Survey Results

Plate I shows the location of the resistivity lines, superimposed on a geologic/topographic base map of the Colado area. The observed data are shown on Figures 2 through 6 with the interpreted resistivity distribution derived from modeling the field data. A two-dimensional IP-Resistivity program developed at the Earth Science Laboratory (Killpack, 1979) was used in the numerical modeling. While the computed models give a good fit to the observed data, they are non-unique. The resistivity sections on Figures 2 through 6 are from numerical models chosen as best fits to the observed apparent resistivity field data. Appendix Figures Al through A5 show calculated resistivities based on these same models for comparison purposes.

#### L'ine D

This line (Figure 2) is at the northernmost end of the geothermal area and extends west from the range front. It was located for close proximity to drill holes 14-22, 13-26, and IGH-1; these holes have the highest recorded temperatures, to date, within the geothermal area. The observed data show a major resistivity discontinuity, interpreted as a fault, near station 3 NW. A conductive zone (<10 ohm-meters) also lies at depth beneath this station. A major change in topography south of station 1 SE introduces topographic effects in the field data.

Modeling results show that sharp contrasts (greater than a factor of 2) in resistivity occur between stations 4-5 NW, 3-4 NW, 2-3 NW, and 0-1 NW. These resistivity discontinuities are interpreted as faults. Only the discontinuity near station 0 corresponds to mapped structures.



ŧ

10 - Intrinsic Resistivity (ohm-m) a = 1000 ft.

1

Ľ

.

4



FIGURE 2 INTERPRETED RESISTIVITY SECTION AND OBSERVED APPARENT RESISTIVITY

LINE D - COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1:24,000

00

Ŧ

Ŧ

Northwest of station 3 NW is a surface layer about 150 feet thick having a resistivity of 10 ohm-meters. Beneath this lies a much thicker (1500 feet) and slightly more resistive (25 ohm-meter) layer. This in turn is underlain by very conductive material (5 ohm-meter) which extends downward to the limit of detectability.

Moderately conductive rocks are indicated at depths greater than 2000 feet in the mountain range between stations 0 to 3 SE. Similar rocks, with a resistivity of about 25 ohm-meters, are within approximately 250 feet of the surface between stations 5 and 6 SE.

Line A

Line A (Figure 3) was located south of, but still near, drill holes 14-22 and 15-21 so that the transmitting electrodes would cover the inferred hot zone which trends southwest from DH 14-22. The observed field data show conductive zones averaging 5-6 ohm-meters at moderate depth overlain by resistive near-surface material at both ends of the line. The central part of the line shows the conductive zone nearer the surface with the resistive zone beneath and extending to depth.

Modeling results show a thin (100 foot) surface layer with a resistivity of 10 ohm-meters extending between stations 1 SE and 2 NW. At 2 NW it apparently thickens abruptly to the northwest. Directly beneath this layer between stations 1 SE and 1 NW is a zone of 4 ohm-meter material with a variable thickness up to about 1000 feet. Between stations 1-2 NW this 4 ohm-meter material extends down a narrow zone to a depth of approximately 1500 feet where it then continues to the northwest. Similar resistivities occur on



Ŧ

€

1

¢

Æ

,C

HING COUNTY, NE Scale 1:24,000

10

ŧ

C

\*

ŧ

the southeast end, coming to within approximately 600 feet of the surface between stations 3-4 SE. A more resistive material (15-35 ohm-meter) occurs near surface between stations 1 and 8 SE. A 15 ohm-meter body also extends to depth beneath and adjacent to the 4 ohm-meter zone noted on the northwest end of the line.

Because the projected trend of high temperatures between drill holes 14-22 and 10-34 crosses Line A near station 0, it could be inferred that the conductive (4 ohm-meter) near-surface layer is indicative of shallow thermal fluids. Lending support to this interpretation is the shallow hot water aquifer shown on a log of drill hole IGH-1 (Getty Oil Co., personal letter). The conduit for these fluids appears to lie between stations 1-2 NW.

#### Line C

This line (Figure 4) extends northwest from Coal Canyon and passes near drill holes 8-34, 9-34 and 10-34. The field data show a conductive (< 5 ohm-meter) zone enclosed by slightly more resistive (5-10 ohm-meter) material at depth beneath stations 0-3 SE. DH 9-34 is located just south of Line C between stations 0-1 SE and is centered on the conductive zone.

Model results show a conductive, approximately 2 ohm-meter, zone at depth which is enclosed by 10 ohm-meter material. This conductive zone occurs at a depth of approximately 1000 feet. The temperature log of DH 9-34 suggests a possible heat source nearby. Thus, the 2 ohm-meter zone may indicate the presence of conductive thermal fluids. No faults are indicated by sharp resistivity contrasts in the data however, so the high temperatures noted are likely due to a pluming effect of thermal fluids down the hydraulic gradient



€

C

Ŧ

€

€

t

€

€

€

E

LINE C - COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1:24,000

within an aquifer.

Line E

This line (Figure 5) is the southernmost line of the survey. Station O lies just north of drill hole IGH-2 (formerly DH 3-10). The field data indicate a resistive surface layer extending approximately from stations 3 NW to 5 SE and appearing thickest in the station interval 1 to 2 SE. Very conductive material is present at a depth of approximately 2000 feet and extends the entire length of the line. This conductive material comes closer to the surface on the northeast end of the line. Faulting is suggested by the field data between stations 5 and 6 SE and is supported by geologic mapping.

The model results show 25 ohm-meter material at the surface between stations 1 to 3 SE. This resistive body is overlain by material more conductive (10 ohm-meter) both to the northwest and southeast. A conductive (2.5 ohm-meter) layer occurs at a depth of about 2000 feet and extends both laterally and downward to the limits of detectability. The very conductive zone between stations 5 and 6 SE is interpreted as higher porosity and/or alteration probably associated with faulting.

Line B

This line (Figure 6) differs from the other lines in that 2000-foot dipoles are used. The observed resistivity values represent the integrated effect of a larger volume of earth, both horizontally and vertically, while the spatial resolution of the interpreted section is only half that of the 1000-foot dipole lines.



€

€

€

£

۲

IO - Intrinsic Resistivity (ohm-m) a = 1000 ft.

€

€

€



FIGURE 5 INTERPRETED RESISTIVITY SECTION AND OBSERVED APPARENT RESISTIVITY LINE E - COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1:24,000

14

€

£.



€

€

a = 2000ft.

€

¢



FIGURE 6 INTERPRETED RESISTIVITY SECTION AND OBSERVED APPARENT RESISTIVITY LINE B - COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1:24,000

15

€

¢

€.

€

C

This profile trends northeast-southwest, subparallel to the dominant structure, and is more influenced by lateral (and non-two-dimensional) geometry within the earth. The line passes close to drill holes IGH-2 and 8-34, and between 17-24 and 18-24. The range front is encountered at about station 0 and the entire northeast end of the line crosses the range. Topographic effects are therefore present in the field data on this end of the line.

The model results show a major resistivity contrast, interpreted as a fault, between stations 0 and 1 SW. This appears to be the range front fault that separates the conductive valley fill with resistivities of 5-10 onm-meters from the rocks of the range which have resistivities upwards of 200-300 ohm-meters. The valley fill is very uniform in resistivity with no anomalous contrasts indicative of buried faulting. The data of this resistivity line do not suggest the presence of a fault extending NW out of Coal Canyon into the valley.

Several resistivity contrasts, interpreted as faults, are noted on the northeast end of the line. Near-surface rocks in this area have resistivities averaging about 200 ohm-meters for the most part. The presence of fairly conductive (25 ohm-meters) areas in the mountain range is of interest. The area at depth between stations 0-2 NE is coincident with the conductive area noted at depth on Line D between stations 1 to 3 SE; the significance of this conductive area is not presently known. The 25 ohm-meter body between stations 4-5 NE may be due in part to lateral effects of alluvium close to the line.

#### DISCUSSION

Plate II is an overlay to Plate I and shows the electrical resistivity distribution at the depth of approximately 1000 feet for each of the five lines. This plate shows the sharp resistivity contrasts and their locations from which the faulting is inferred. The data source for Plate II is the computed models shown as Figures Al through A5. There is good correlation with mapped structures within the mountain range. The detection of suballuvial faults away from the mountain front is of particular importance, for, while these faults may have been suspected, their approximate location was not known. Although shown as separate faults, several could be part of a single fault zone and it must be understood that the locations of these faults as shown on Plate II are to be considered as close approximations only. They are necessarily subject to the sensitivity of the dipole spacing used as well as the non-uniqueness of the computer modeling technique.

Plate III is an overlay to Plates I and II. It shows an interpreted schematic of the hydrothermal reservoir based upon resistivity contrasts. Areas interpreted to contain gravels saturated with thermal waters as well as areas containing the conduits for these waters have been denoted.

#### ACKNOWLEDGEMENTS

This survey was completed with funds provided by the Department of Energy, Division of Geothermal Energy, to the Earth Science Laboratory Division, University of Utah Research Institute under contract number DE-AC07-80ID12079, as part of the Industry Coupled Case Study Program.

Special thanks are given to Dawnetta Bolaris who provided drafting expertise and to Holly Baker who patiently typed this report and its revisions. Thanks are also given to those members of ESL staff who provided a careful review of this report's contents.

#### REFERENCES

- Electrodyne Surveys, 1978, An Electrical Resistivity Survey of the Colado Hot Springs Prospect, Pershing County, Nevada: Volumes I & II submitted to Getty Oil Company: Earth Science Laboratory open-file release (NV/COL/GOC-1).
- Getty Oil Company, 1979, Temperature Logs from Shallow Depth Drill Holes: Earth Science Laboratory open-file release (NV/COL/GOC-3).
- Killpack, Terry J., Hohmann, Gerald W., 1979, Interactive Dipole-Dipole Resistivity and IP Modeling of Arbitrary Two-Dimensional Structures: Univ. of Utah Res. Inst., Earth Science Laboratory report 15, 120 p.
- Sibbett, Bruce S., Bullett, Michael J., 1980, Geology of the Colado Geothermal area, Pershing County, Nevada: Univ. of Utah Res. Inst., Earth Science Laboratory report 38, 34 p.

### APPENDIX

## Computed Resistivity and Interpreted Sections



€

ŧ

ſ



FIGURE A1 INTERPRETED RESISTIVITY SECTION AND COMPUTED APPARENT RESISTIVITY LINE D - COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1: 24,000

21

€

€

C

ŧ



C

€

E

•

ť

ť



FIGURE A 2 INTERPRETED RESISTIVITY SECTION AND COMPUTED APPARENT RESISTIVITY LINE A - COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1: 24,000

22

ŧ

C



C

ŧ

Ľ

P(ohm-m)

**'**0.

15

C

(

×э

Э

Э

INTERPRETED RESISTIVITY SECTION AND COMPUTED APPARENT RESISTIVITY FIGURE A3 LINE C - COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1:24,000



C

€

€

24

C

ť

E

€

IO=Intrinsic Resistivity (ohm-m) a=I000 ft.

t

1

6



FIGURE A4 INTERPRETED RESISTIVITY SECTION AND COMPUTED APPARENT RESISTIVITY LINE E-COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1: 24,000 LINE B

C

t

ł

€

ŧ

Č





FIGURE A5 INTERPRETED RESISTIVITY SECTION AND COMPUTED APPARENT RESISTIVITY LINE B-COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA Scale 1:24,000

25

€

€



## Plate I



Shaft



# PLATE II INTERPRETED ELECTRICAL RESISTIVITY DISTRIBUTION at a DEPTH of 1000 FEET COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA

SCALE 1:24,000

R. 33

 $\begin{array}{c} | 0 < \rho \leq 25 \\ 25 < \rho \leq 50 \\ 50 < \rho \leq 125 \\ \rho > 125 \\ \end{array}$ 

EXPLANATION (ohm-m)

 $\rho \leq 5$ 

 $5 < \rho \le 10$ 

40° 15'-

28 N.

PLATE II

27 N

<u>R.33E.</u>



# PLATE III

## EXPLANATION

R. 33E.



Deep low resistivity zone (Possible deep reservoir area) Shallow low resistivity zone (Possible shallow plume) Probable feeder zones for thermal fluids

PLATE III INTERPRETED SCHEMATIC of HYDROTHERMAL RESERVOIR (FROM RESISTIVITY DATA) COLADO GEOTHERMAL AREA PERSHING COUNTY, NEVADA SCALE 1: 24,000 40° 15' ----