

MOANA SWIMMING POOL  
GEOTHERMAL WELL  
CONSTRUCTION AND TESTING

Project No. 81-195

Prepared for:

CITY OF RENO

July 15 , 1981

Prepared by:

Dale C. Bugenig  
Dale C. Bugenig

Deborah L. Cave  
Deborah L. Cave

Reviewed by:

William E. Nork  
William E. Nork



**WILLIAM E. NORK, Inc.**

## TABLE OF CONTENTS

	Page
1.0 SUMMARY AND CONCLUSIONS .....	1
2.0 INTRODUCTION .....	2
3.0 CONSTRUCTION CHARACTERISTICS .....	4
3.1 WELL CONSTRUCTION .....	4
3.2 TEMPERATURES MONITORED DURING CONSTRUCTION .....	6
4.0 TESTING OF THE WELL .....	10
4.1 STEP-DRAWDOWN TESTING .....	10
4.2 CONSTANT-DISCHARGE TESTING .....	13
5.0 HYDROGEOLOGY .....	21
6.0 YIELD RATING OF WELL .....	22
7.0 CHEMICAL QUALITY OF WATER FROM WELL .....	23

### SOURCES OF INFORMATION

- APPENDIX A LITHOLOGIC LOG OF THE BOREHOLE AND GEOPHYSICAL LOGS
- APPENDIX B CONSTRUCTION SUMMARY AND DRILLER'S REPORT
- APPENDIX C TEST PUMPING DATA

### FIGURES AND TABLES:

FIGURE 1. LOCATION MAP OF THE MOANA POOL GEOTHERMAL WELL .....	3
FIGURE 2. CONSTRUCTION DIAGRAM OF MOANA POOL GEOTHERMAL WELL .....	7
FIGURE 3. MOANA POOL GEOTHERMAL WELL TEMPERATURE LOG OF FLUID-FILLED HOLE .....	9
FIGURE 4. MOANA POOL GEOTHERMAL WELL STEP-DRAWDOWN TEST 0830 HRS. - 0030 HRS., 6/9-10/81, DRAWDOWN AND RECOVERY DATA .....	11
FIGURE 5. MOANA POOL GEOTHERMAL WELL STEP-DRAWDOWN TEST 0830 HRS. - 0030 HRS., 6/9-10/81 DRAWDOWN DATA .....	12
FIGURE 6. SPECIFIC CAPACITY AND YIELD VERSUS DRAWDOWN DATA, MOANA POOL GEOTHERMAL WELL .....	14



**WILLIAM E. NORK, Inc.**

TABLE OF CONTENTS (continued)

	Page
FIGURE 7. WELL LOSS ANALYSIS, MOANA POOL GEOTHERMAL WELL .....	15
FIGURE 8. COMPARISON BETWEEN OBSERVED AND THEORETICAL DRAWDOWN, MOANA POOL GEOTHERMAL WELL .....	16
FIGURE 9. MOANA POOL GEOTHERMAL WELL CONSTANT- DISCHARGE PUMPING TEST, 2000 HRS., 6/10/81 TO 2000 HRS., 6/11/81, SEMI-LOG PLOT OF DRAW- DOWN DATA .....	17
FIGURE 10. MOANA POOL GEOTHERMAL WELL CONSTANT- DISCHARGE PUMPING TEST, 2000 HRS., 6/10/81 TO 2000 HRS., 6/11/81, LOG-LOG PLOT OF DRAWDOWN DATA .....	18
FIGURE 11. MOANA POOL GEOTHERMAL WELL CONSTANT- DISCHARGE PUMPING TEST, 2000 HRS., 6/11/81 TO 0800 HRS., 6/12/81, SEMI-LOG PLOT OF RESIDUAL- DRAWDOWN DATA .....	19
 TABLE 1. TEMPERATURE OF DRILLING FLUID AT VARIOUS DEPTHs DURING ROTARY-MUD DRILLING OF THE MOANA POOL GEOTHERMAL WELL .....	8
TABLE 2. RESULTS OF STEP-DRAWDOWN TEST .....	10
TABLE 3. TRANSMISSIVITY VALUES DETERMINED FROM PUMPING TEST DATA .....	20
TABLE 4. CHEMICAL QUALITY DATA, MOANA POOL GEOTHERMAL WELL .....	23



**WILLIAM E. NORK, Inc.**

## 1.0 SUMMARY AND CONCLUSIONS

1. A 469.7-foot deep geothermal well was constructed in the northwest corner sun deck of the City of Reno Moana Pool located in southwest Reno, Nevada. The well was constructed so as to derive geothermal water for potential use as a source of heat for the swimming pool.
2. The well was test-pumped at the rates of 100, 150, 200 and 250 gpm for a period of 4 hours each, respectively, on June 9 and 10, 1981. A 24-hour constant-discharge pumping test at a pumping rate of 200 gpm was performed June 10 and 11, 1981. Temperature of the discharge water remained a constant 127.4°F throughout testing.
3. Bottom-hole (469.7 feet) temperature after the hole had stabilized was measured at 124.7°F. The hole is approximately isothermal below a depth of 400 feet.
4. Test data indicate that the well is capable of yielding up to 1200 gallons per minute of 127.4°F ground water.
5. Water chemistry data indicate that precipitation of silica or calcium carbonate in the well or heat exchanger does not appear to be a problem.
6. The chemical quality of the water does not meet state and federal drinking-water standards. However, water quality appears to be sufficiently good for direct use of the water for purposes of heating the swimming pool and space heating of the buildings. Direct use of the water would allow for a more efficient heating system.




## 2.0 INTRODUCTION

In summer of 1979 a test well was drilled at the Moana Pool Facility in southwest Reno to assess the potential of deriving an adequate supply of sub-surface, geothermal water for purposes of heating the pool facilities. Data collected during this program were evaluated and from these data the pool heating system appeared feasible (WEN, INC., 1979 and OIT, 1979). In January, 1981, WILLIAM E. NORK, INC., was contracted by the City of Reno to supervise drilling, construction, and testing of a production geo-thermal well at the same site. Aqua Drilling and Well Service, Sparks, Nevada, was contracted to construct and test the well.

The Moana Swimming Pool geothermal well is located in the NE $\frac{1}{4}$ , NE $\frac{1}{4}$ , NW $\frac{1}{4}$ , Section 25, T. 19 N., R. 19 E., in southwest Reno (Figure 1). The well was completed to a depth of 469.7 feet on May 29, 1981. Ultimate construction design of the well was based on types of geologic materials penetrated, geophysical logs of the borehole, and data collected during drilling of the test and production holes.

Upon completion of well construction a test pump was installed and a series of aquifer/pumping tests were performed. This report describes in detail the construction of the well and the results of testing.





Map base: Mt. Rose NE, Nevada USGS 7.5 - minute topographic map

SCALE 1:24 000




FIGURE . 1 Location map of the Moana Pool Geothermal Well.

### 3.0 CONSTRUCTION CHARACTERISTICS

#### 3.1 WELL CONSTRUCTION

Drilling of the Moana Pool geothermal production well commenced on May 18, 1981. A  $17\frac{1}{2}$ -inch diameter hole, using the rotary-mud method, was drilled to a depth of 10 feet, and a temporary 16-inch conductor casing was installed from 2.26 feet above ground level to 7.74 feet below the surface. A nominal 14-inch diameter hole was then drilled to a depth of 120 feet, and  $10\frac{1}{4}$ -inch O.D. x 0.211-inch wall thickness steel casing was installed. A cement grout seal was emplaced in the annular space between the casing and borehole wall using a tremie pipe. The seal was placed from a depth of 115 feet to ground surface in order to prevent mixing of shallow and cooler ground water with the geothermal waters at depth.

A nominal 10-inch hole was drilled from 120 to 138 feet by the air-rotary method. Sloughing of the sands and gravels necessitated returning to the rotary-mud method. Drilling continued to a depth of 165 feet, but continual sloughing problems indicated that the hole had not stabilized and that erosion of the borehole may have occurred. To prevent possible collapse and ultimate loss of the hole, a cement drill plug was emplaced for the purpose of stabilizing the hole on May 26, 1981, to a depth of 165 feet. The cement was allowed to set up overnight, and was drilled through on the following day.

Drilling of a nominal 10-inch diameter borehole by the air-rotary method was resumed on May 27, 1981, but sloughing of the formation material resulted in discontinuing air-rotary drilling at 180 feet. The air-rotary method had been selected as the preferred method of drilling in the potential production zones because of the anticipated problems associated with removing of mud-based drilling fluids from a geothermal formation.

Using the rotary-mud method, drilling continued from a depth of 180 feet to the original target depth of 300 feet. The 300 feet depth was reached on May 28, 1981. The hole was geophysically logged (Appendix A) and lithologic samples of the materials penetrated during drilling were examined. Evaluation of data indicated that the probable yield of a well completed to this depth would not exceed 50 gpm because of the large percentage of clay in the formation. The composite water temperature recorded at this depth was 95.6°F. On the basis of this evaluation, WILLIAM E. NORK, INC., recommended additional drilling to a depth of about 500 feet.



The final 180 feet of the Moana well was drilled on May 29, 1981. Drilling was terminated in an impermeable clay bed at 480 feet. An abbreviated lithologic log of the Moana Pool geothermal well is as follows:

<u>Depth Interval (feet)</u>	<u>Lithology</u>
0-90	unconsolidated black volcanic sands and gravels, angular; minor quartz and green chert sands; per cent brown clay increasing with depth.
90-170	fine- to medium-grained volcanic sands, semi-angular; reduction in amount of clay.
170-320	fine- to medium-grained semi-angular black and green volcanic sands, interbedded with clay lenses, clayey sands and silts.
320-375	micas, quartz and volcanic sands, .05 inch average diameter; large reduction in amount of clays.
375-445	consolidated sands, one-inch average diameter; clay minor.
445-480	interbedded unconsolidated quartz and volcanic sands with clay lenses and clayey sands, clay increasing with depth.

Preliminary well design called for nominal 10-inch casing to 120 feet depth and nominal eight-inch casing from 120 to total depth. Primary purpose of the 10-inch casing in the upper 120 feet was simply to provide sufficient room to house an eight-inch pump. Smaller diameter casing and well screen below this depth would allow more than adequate flow of water into the well and provide for an overall cost savings. Johnson-UOP shaped wire wound well screen was selected because it contains more open area per linear foot than any other screen design. Large open area provides for low entrance velocity of water into the well through the well screen. Low entrance velocity results in high-well efficiency (lower pumping cost per gallon of water), and reduces the potential for chemical incrustation or corrosion of the well.

Final well design was based on lithologic samples of the formation materials penetrated, the driller's log, borehole geophysical logs, and temperature surveys of the borehole. The interval 355 to 455 feet depth was selected for installation of well screen. The well-sorted nature of the formation materials



in this zone and their grain-size distribution permitted installation of 30 slot screen (0.030 inch slots) and development of a natural gravel pack. Because of approximately ten feet of fill at the base of the hole, the bottom of the 8-5/8-inch casing was set at a depth of 469.7 feet.

Final well construction is shown in Figure 2. Lithologic and geophysical logs are summarized in Appendix A, and copies of the Driller's Report to the State Engineer and WEN, Inc.'s Well Construction Summary are included in Appendix B.

Using a drill-rig mounted air compressor, the well was developed for nine and one-half hours on June 8, 1981. Development of a well is undertaken in order to remove drilling fluid from the well bore and to break down the mud cake adhering to the borehole walls. When development of a well is effective, flow of water to the well is unrestricted. In addition, development often results in removal of fine sands and silt from the immediate vicinity of the borehole. Such action increases the effective radius of the well. In the case of the Moana Well discharge water at the completion of development had no odor or taste and was clear of sediment. The development work was, therefore, believed to be successful.

On June 16, 1981, (at the completion of test pumping of the well), 2 gallons of sodium hypochlorite were added to the well to produce a concentration of 200 gpm chlorine for purposes of disinfecting the well. After setting for 24 hours, the well was pumped free of all residual chlorine on June 17, 1981. Test pumping equipment was then removed and the bottom of the well was sounded. The well was open to 469.7 feet with only an insignificant amount of fill at the base of the 10-foot sediment trap (blank casing) located below the screen. A steel plate was then welded to the top of the casing to prevent vandalism and contamination.

### 3.2 TEMPERATURES MONITORED DURING CONSTRUCTION

Temperature of the drilling fluid at various depths within the borehole was monitored during well construction. Cool drilling fluids and adjacent formation waters do not equilibrate thermally in short periods of time due to the rate of circulation of fluid within the hole. Therefore, drilling fluid temperatures which were measured were generally lower than the actual water temperatures of formation. Nevertheless, they are indicative in a qualitative sense of changes in formation water temperature (see Table 1).



**Figure 2. Construction diagram of  
Moana Swimming Pool Geothermal Well.**




Table 1. Temperature of drilling fluid at various depths during rotary-mud drilling of the Moana Pool Geothermal Well.


<u>Depth (feet)</u>	<u>Temperature (°F)</u>
175	107.6*
190	82.4
245	89.6
265	93.2
290	94.1
375	95.0
445	96.8
465	97.7
475	98.6

\*Temperature measured during air-rotary drilling.

On May 28, 1981, WILLIAM E. NORK, INC., conducted an initial temperature survey using a Keck DTM-75 Temperature Logging System. Bottom hole (290 feet) temperature was measured at 95.6°F (Figure 3). From results of this survey and data from the geophysical log of the borehole and formation cuttings, it was decided to drill to a depth of about 500 feet (3.1, above).

A second temperature log of the deepened hole was then run on May 30, 1981 (Figure 3). The temperature gradient in the upper 300 feet of the hole was approximately 7 °F per 100 feet, dropping to 5°F per 100 feet from 300 to 400 feet below L.S.D. At depths greater than 400 feet, the temperature became approximately isothermal. Bottom hole (469.7 feet) temperature prior to installation of well casing and development was measured at 120.1°F.





#### 4.0 TESTING OF THE WELL

After completion of construction and development of the well, a 5-stage Red Jacket turbine pump equipped with a 25-horsepower Hitachi submersible motor was installed in the well by Aqua Drilling and Well Service on June 7, 1981. The pump intake was set at a depth of 194 feet below L.S.D. (land surface datum). Pump installation included a 3/4 inch diameter stilling well to assure accurate measurement of water levels in the well during testing. Development consisted of alternately surging and pumping of the well until water discharge was clear and sand-free.

Upon completion of developmental pumping, step-drawdown and constant-discharge pumping tests were performed.

##### 4.1 STEP-DRAWDOWN TESTING

A 16.5-hour four-step-drawdown test was conducted June 9 and 10, 1981. Testing results are illustrated in Figures 4 and 5 and summarized in Table 2 and Appendix C.

Static water level prior to testing was 20.06 feet below L.S.D. Testing commenced at 0830 hours June 9, 1981. Well was pumped at rates of 100, 150, 200, and 250 gpm. Testing terminated at 0030 hours June 10, 1981. Recovery of water levels in the well was rapid, approximately 91 per cent in 12 hours.

Table 2. Results of step-drawdown test.

Step	Pumping Rate (gpm)	Step Duration (minutes)	Water Level (feet)	Drawdown (feet)	Specific Capacity (gpm/ft)
I	100	240	42.44	22.38	4.47
II	150	240	57.86	37.80	3.97
III	200	240	74.36	54.30	3.68
IV	250	270	80.21	60.15	4.16






FIGURE . 4 Moana Pool Geothermal Well step drawdown test,  
0830 hrs-0030 hrs 6/9-10/81 drawdown and  
recovery data.

K-E SEMI-LOGARITHMIC 4 CYCLES X 70 DIVISIONS  
KEUFFEL & ESSER CO. MADE IN U.S.A.

46 6010




FIGURE 5 Moana Pool Genthal Well step drawdown test  
0830 hrs-0030 hrs 6/9-10/81, drawdown data.

Temperature of discharge water during each step in the drawdown test remained a constant 51.5°C (124.7°F).

Step-drawdown test results indicate that additional well development occurred during the last step (250 gpm) of the test. During this step there was an abrupt rise in pumping water level, a decrease in drawdown, and an increase in the specific capacity (Figure 6). These effects suggest the collapse and removal of a "bridge" of formation fines which may have been plugging the formation. Step-drawdown test data were used to evaluate well efficiency prior to additional development of the well (Figures 7 and 8). The well loss analysis indicates that well efficiency improved near the end of step-drawdown testing. This is illustrated by the observed well efficiency of greater than 95 per cent compared to a theoretical well efficiency of about 80 per cent during the final step.

#### 4.2 CONSTANT-DISCHARGE TESTING

A 24-hour (1440 minutes) constant-discharge test at a pumping rate of 200 gpm was conducted June 10 and 11, 1981, followed by 12 hours of recovery water level measurement. Test data are illustrated in Figures 9, 10 and 11 and summarized below:

Static water level prior to testing was 21.74 feet below top of stilling well. Testing commenced at 2000 hours June 10, 1981. At the end of 24 hours drawdown was 46.76 feet, pumping water level was 68.50 feet, and specific capacity was calculated to be 4.28 gpm/ft. Testing terminated at 2000 hours June 11, 1981. Recovery of water levels in the well was rapid, approximately 96 per cent within 12 hours.

Appendix C contains constant-discharge pumping test drawdown and recovery data sheets.

Transmissivity, the overall ability of the aquifer to transmit ground water, was determined through analysis of the constant-discharge test data by the Theis non-steady state artesian aquifer equation, the Cooper-Jacob-straight-line approximation of the Theis equation, and Hantush-Jacob non-steady state leaky artesian aquifer equation (Lohman, 1972). The Theis equation describes the radial flow of ground water to a pumped well in an idealized artesian aquifer. When the artesian aquifer in which a well is completed is bounded above and/or below by a semi-permeable bed or aquitard, pumping of the well may induce vertical flow through such confining semi-permeable beds. This is referred to as "leakage". Calculated transmissivity values are summarized in Table 3.






FIGURE . 6 Specific capacity and yield versus drawdown data,  
Moana Pool Geothermal Well.




FIGURE .7 Well loss analysis, Moana Pool Geothermal Well.






FIGURE .8 Comparison between observed and theoretical drawdown.  
Moana Pool Geothermal Well








Table 3. Transmissivity values determined from pumping test data.

Method	Aquifer Type	Data	Transmissivity (gpd/ft/day)
Cooper-Jacob approximation	non-leaky artesian	drawdown	7892
Cooper-Jacob approximation	non-leaky artesian	residual drawdown	8250
Hantush-Jacob (and Theis)	Leaky artesian	drawdown	6741

Aquifer storage coefficient could not be calculated due to an absence of observation well data.



## 5.0 HYDROGEOLOGY

In the southwest Reno area, geothermal ground water rising through faulted Tertiary bedrock units is confined below a widespread characteristically blue clay strata. The geothermal water, inhibited from upward movement, moves laterally through permeable deposits of sands and gravels. The base of this confining clay layer was reached at approximately 310.0 feet depth during drilling of the Moana Pool well. Penetration of the confining bed was accompanied by an increase in the composite water temperature above that measured during drilling of the initial 300 feet.

Analysis of test data suggests that the aquifer tapped by the Moana Pool well may be characterized as a leaky artesian aquifer. Transmissivity data indicates that the geothermal aquifer tapped by the well is sufficient to meet the long-term water-supply requirements of the project.



## 6.0 YIELD RATING OF WELL

Data collected during the pumping tests may be used to rate the performance of the well. The 24-hour specific capacity of the well calculated from the constant-discharge test data was 4.28 gpd/ft. Given a static water level of 20 feet below L.S.D. and a maximum potential drawdown of 290 feet (drawdown to top of the major hot water-bearing strata), the well could yield up to approximately 1,200 gallons per minute of ground water at temperatures of 53°C (127.4°F). Pumping water levels will be correspondingly higher in the well at lower pumping rates. They may be approximated by:

$$h = \frac{Q}{4.28 \text{ gpm/ft}} + 20 \text{ ft.}$$

where  $h$  = pumping water level below L.S.D. (feet)

$Q$  = pumping rate (gpm)

Therefore, at a peak pumping rate of 125 gpm, the pumping water level in the well will be approximately 49.2 feet below L.S.D. Pumping water levels should remain relatively stable due to the nature of the aquifer.



## 7.0 CHEMICAL QUALITY OF WATER FROM WELL

A water sample for chemical analysis was collected (on June 11, 1981) at the conclusion of constant-discharge testing. Results of the analysis are given in Table 4.

Table 4. Chemical quality data, Moana Pool Geothermal Well

(all constituents reported as milligrams per liter, unless otherwise noted)

		Drinking Water Standard
Temperature (°C)	53.0	
Field pH (pH units)	7.76	
Lab pH (pH units)	8.1	
Field Conductivity ( $\mu\text{MHO}/\text{cm}$ )		
Hardness (as $\text{CaCO}_3$ )	58	
Alkalinity	117	
Total Dissolved Solids	624	
-Ca	21	
Mg	0.9	150 <sup>2</sup>
Na	160	
K	8.2	
Fe	0.03	0.6 <sup>2</sup>
Mn	0.03	0.1 <sup>2</sup>
$\text{SO}_4$	218	500 <sup>2</sup>
Cl	28	400 <sup>2</sup>
F	< 2.7*	1.4-2.4 <sup>1</sup>
$\text{NO}_3$	0.1	10 <sup>1</sup>
$\text{PO}_4$	0.03	
As	0.10*	0.05 <sup>1</sup>
Ba	< 0.05	1.0 <sup>1</sup>
B	1.2	
Cd	< 0.01	0.01 <sup>1</sup>
Cr	< 0.02	0.05 <sup>1</sup>
Bb	< 0.05	0.05 <sup>1</sup>
Hg	< 0.0005	0.002 <sup>1</sup>



Table 4. (continued)

		Drinking Water Standard
Se	<0.005	0.01 <sup>1</sup>
Ag	<0.01	0.05 <sup>1</sup>
Cu	<0.02	1.0 <sup>1</sup>
Zn	0.01	5 <sup>1</sup>
SiO <sub>2</sub>	83	

\* exceeds Drinking-Water Standards.

1. USEPA Primary Drinking-Water Standards.

2. State of Nevada Secondary Drinking-Water Standards.

Review of the results of the chemical analysis indicates that the water does not meet State of Nevada Drinking-Water Standards. However, direct use of the water in the swimming pool may be permissible.

Detailed analysis of the water chemistry results provide some salient findings. The water is under-saturated with silica at temperatures down to about 8°C (46.4°F). Therefore, precipitation of silica in the well or within the heat exchanger itself does not appear to be a problem. The ground water is only slightly saturated with respect to calcium carbonate at the ambient ground-water temperature. However, potential for precipitation of calcite within the well or heat exchanger is minimal.



## SOURCES OF INFORMATION

Bugenig, D. C., 1979, "Geothermal Exploration Moana Pool Site, Reno, Nevada"; private report prepared for Oregon Institute of Technology, Klamath Falls, Oregon, prepared by WILLIAM E. NORK, INC.

Bruin, J. and Hudson, H. E., 1961, "Selected Methods for Pumping Test Analysis"; Illinois State Water Survey, pp. 30-37.

Lohman, S. W., 1972, "Ground-Water Hydraulics"; U.S.G.S. Professional Paper 708.

Driller's Report to the State Engineer's Office.

U.S.G.S. Mount Rose N.E., Nevada 7.5-minute Topographic Quadrangle.



**WILLIAM E. NORK, Inc.**

APPENDIX A

LITHOLOGIC LOG OF THE BOREHOLE AND  
GEOPHYSICAL LOGS



**WILLIAM E. NORK, Inc.**

# LOG OF BOREHOLE

BOREHOLE 81-195  
PAGE 1 OF 4

LOCATION	LOG. or COORDS.		DRILLER		START DATE	FINISH TIME
	Moana Pool		Aqua Drilling and Well Service			
LOGGED BY	T.G. Maggio	GROUND ELEV.	469.7'	RIG	Ingersoll-Rand Cyclone TH6	
		TOTAL DEPTH	469.7'	BIT(S)	17.5" (ACL 422); 13 3/4" (422)	
		BOREHOLE DIAM.	17 1/2" o-10' 13 3/4"	FLUID	Bentonite; 9 7/8" (6325)	
			10-11 1/2"; 9 7/8" 120-469.7'			
DEPTH	DEPTH RATE	CIRC. BILIFT ft/min (m/min)	MATERIAL	SYN. BBL	DESCRIPTION AND COMMENTS	
20'		N/A				
25'						
35'					Qtz, black-purple volcanic fragments, biotite frags, pyrite, assorted other rock frags; chert, chaledony, greenstone, med-grained to cobble sized, mostly angular.	
55'					Lithology similar to that above but with some clay fragments. Grain Size Ranges from cobbles & coarse sands to clay sized particles.	
65'					Mainly quartz and volcanics with the addition of more clay fragments. Pyrite disappeared. Clay is tan colored and crumbles in the fingers.	
75'					Lithology similar to that of above but overall grain size becoming smaller (finer). Grains angular to sub-rounded. Assorted rock frags included.	
90'					Drilling becomes slower in this zone. Formation harder. Lithology similar to descriptions above but becoming more clayey. Qtz, granite frags, cherts, black volcs, chaledony, clay frags.	
100'					Lithology same as above but becoming less clayey. Drilling not as hard, smoothing out at a steady rate. Mostly black volcanic frags.	
120'					Lithology same as above but w/ less clays. Qtz, black volcs, granite/diorite frags, Assorted rock & mineral frags: greenstones, biotite, chaledony. fine to med grained, sub-rounded to angular.	
1100'					Blow >100+ gpm @ 42°C - gravel + sand.	

PROJECT 81-195

Scale:  
1" = 20'

7.5'  
 ~1'  
 >1'  
 clay

## LOG OF BOREHOLE

BOREHOLE 81-195

PAGE 2 OF 4

LOG. or COORDS.	DRILLER	SPARKS	RIG	BIT(S)	FLUID	START	FINISH
						DATE	TIME
GROUND ELEV.	AQUA DRILLER				BENTONITE		
TOTAL DEPTH	470'						
BOREHOLE DIAM.							
DEPTH	PENE. RATE	CIRC. BILIFT ft (cm) (ft/m)	MATERIAL	SYMBOL	DESCRIPTION and COMMENTS		
140			Sand & sandy clay		clayey sand some yellow + "blue" clay sloughing badly from above. Much of the clay is washing out and cuttings are being circulated thru mud pump.		
160					more of same. recirculated cuttings a real problem. Fouling jets on bit & interfering w/ pump operations.		
170					Brown - grey clay matrix. Black, green & red volc sands. Minor green chert. .2" & .1" are dia. Interbedded clays & clayey sands.		
180					Clay matrix predom. Volc & gl. sands + chert grains. .05", .2", .8" are dia - larger sand grains in sample because 170-180 are blown. Semi-Ang. .8" (gravel) probably sloughing from above. Frag of concrete probably from partially (?) destroyed cement filling of possum belly $T = 42^\circ\text{C}$		
205					Volc sands + minor gl. - interbedded grey clay & clayey sands 90-95% gro. .05" are dia (size decreased because switched from air to mud drilling). Semi-Ang. sands, $T_{190-210} = 28^\circ\text{C}$ (mud). Additional bag of bentonite added at 200'. Additional bag of bentonite added at 200'.		
230'					Black & green Volc sands + gl. gro. Semi-ang. Extremely clayey drill bailing up. Added detergent at 215'. Grain size increased to .1" ave (due to increase in viscosity of mud?).		
240'					Clay decreased slightly - dulling faster		
265'					90% gro. Clay in sample vs. clay mud. Drilling again slowing down - increase in clay. Semi-ang sand gro. of volc sands + minor gl. & chert. 2 sizes: .05" and .1" ave. $T_{245-250} = 32^\circ\text{C}$		
					Clay lenses + clayey sands. .05" are dia. Larger population diminished. $T_{265-270} = 34^\circ\text{C}$ $T_{270-275} = 35^\circ\text{C}$		

PROJECT 81-195

LOCATION SW Remer  
LOGGED BY DCC

$$1'' = 20'$$

## LOG OF BOREHOLE

~~BOREHOLE 8~~ MOANA POOL 81-195  
PAGE 3 OF 4

LOG. or COORDS.	DRILLER	START	FINISH		
GROUND ELEV.	RIG	DATE			
TOTAL DEPTH	BIT(S)	TIME			
BOREHOLE DIAM.	FLUID	SEOPHYS LOG	YES — NO		
		HOW LEFT			
280'					
SW Remo					
DLC					
LOCATION					
LOGGED BY					
PROJECT					
81-195					
410'					
DEPTH	PENE. RATE	CIRC SHELF (1000 ft/min)	MATERIAL	SYMBOL	DESCRIPTION and COMMENTS
300'					Clay lenses + clayey sands. .05" ave dia, larger population (.1") diminished $T_{265-270} = 34^{\circ}\text{C}$ $T_{290-295} = 35^{\circ}\text{C}$ Ended 1 section of drilling Began drilling
310'					
315'					Grey clay + white Sands .05" & .1" ave dia.
320'					Large reduction in amt of clay. Cuttings are 55% minor clays. 80-90% grs. Ang → Semi-Ang. Volcanics, gyps. spicas. Extremely fine-grained sands (.01" ave dia) from 320-330'. .05" dia again at ~ 325' becoming predominant after 330'. Unconsolidated material (drilling slowed down) hit at 345'
					$T_{360-365} = 34^{\circ}\text{C}$
370'					95% Grs. Sub-Ang. Clays greatly diminished. Grs. slightly larger .1" ave. dia. Consolidated sands hit at 375'. $T_{375-380} = 35^{\circ}\text{C}$
380'					90-95% Grs. Definite greenish sands. .05"- .1" ave. dia. from 380-390'; losing predominance w/ .05" dia after 390'. $T_{415-420} = 35^{\circ}\text{C}$

# LOG OF BOREHOLE

BOREHOLE Moana Pool 81-195  
PAGE 4 OF 4

LOCATION LOGGED BY	LOG or COORDS.					DRILLER	START	FINISH
	GROUND ELEV.					RIG	DATE	
	TOTAL DEPTH					BIT(S)	TIME	
	BOREHOLE DIAM.					FLUID	GEOPHYS LOG	YES NO
SW Reno DLC	DEPTH	PENE RATE	CIRC. ft. (m) g (mm)	BILIFT ft. (m)	MATERIAL	SYN- COL	DESCRIPTION AND COMMENTS	
410'							90-95% Grs. Definite green chert sands .05"-1" ave. dia. from 380-390'. Lining predominance of .05" dia. after 390' $T_{415-420} = 35^{\circ}\text{C}$	
445'							After 445', again began hitting distinct clay beds Qtz sands & monomineralic grains seen to be increasing. Clay again predominant. $T_{465-470} = 36.5^{\circ}\text{C}$	
480'								
PROJECT 81-195								

APPENDIX B


CONSTRUCTION SUMMARY AND DRILLER'S REPORT



**WILLIAM E. NORK, Inc.**

WELL Moana Pool Geotherm

## WELL CONSTRUCTION SUMMARY



LOCATION Moana Pool SW Remote  
PERSONNEL T J DCB DLC

LOCATION & COORDS: NE<sup>1/4</sup>, NE<sup>1/4</sup> NW<sup>1/4</sup>  
Sec. 25, T.19 N., R.19 E.

ELEVATION: GROUND LEVEL \_\_\_\_\_  
TOP OF CASING \_\_\_\_\_

### DRILLING SUMMARY:

TOTAL DEPTH 469.7 T.D.

BOREHOLE DIAMETER 17 1/2" O.D. - 10 3/4"  
10-118'; 9 7/8" 120-469.7'

DRILLER Aqua Drilling & Pump Service  
Sparks, NV

RIG Ingersoll-Rand Cyclone TH 60  
BIT(S) 17 1/2" (ACG 422); 13 3/4" (422)  
9 7/8" (# 6325)

DRILLING FLUID Bentonite

SURFACE CASING 16" O.D.; +3.5' to -6.5'

### WELL DESIGN:

BASIS: GEOLOGIC LOG ✓ GEOPHYSICAL LOG ✓

CASING STRING(S): C=CASING S=SCREEN

+1 - 118' C1

90 - 359.7 C2

359.7 - 459.7 S1

459.7 - 469.7 C2

— — — — —

— — — — —

— — — — —

— — — — —

CASING: C1 10 3/4" O.D. x 0.210" wall

C2 8 5/8" O.D. x 0.270" wall

C5

C4

SCREEN: S1 8" pipe size Johnson #30

S2

S3

S4

CENTRALIZERS None

FILTER MATERIAL None (natural gravel pack)

CEMENT 5170 lbs. cement in annular space from 118' to surface

OTHER drill plug 3 yd<sup>3</sup> 165' to 20' (requested only 1.5 yd<sup>3</sup> for 165' to 118')

### CONSTRUCTION TIME LOG:

TASK	START	DATE	TIME	FINISH
	DATE	TIME	DATE	TIME
DRILLING:				
17 1/2"	5/18/81			5/18/81
13 3/4"	5/19/81	1600	5/19/81	2000
9 7/8"	5/22		5/29/81	1810
GEOPHYS. LOGGING:	5/28	1330	5/28	1400
CASING:	5/30	730	5/30	900
10 3/4" (C1)	5/19/81	830	5/19/81	1145
8 5/8" (C2)	5/30/81	1145	6/12/81	0921

FILTER PLACEMENT	NONE			
CEMENTING:	5/21/81	1415	5/21/81	1445
DEVELOPMENT:	6/2/81	1000	6/11/81	2000
OTHER:	drill plug	5/26/81 0945	5/26/81	1020

### WELL DEVELOPMENT

Blow screened interval & drill rig mounted compressor - no dispersant

### COMMENTS:

Cement installed via tremie pipe from 118' to surface to seal off cooler water.

Attempt to drill & air below 118' foiled by loose formation & caving

Johnson Figuri "K" Packer

Scale:

1" = 50'

Log No.....  
Permit No.....  
Basin.....

**WELL DRILLERS REPORT**

Please complete this form in its entirety

1. OWNER City of Reno

ADDRESS Moana Pool - Moana Ln, Reno

2. LOCATION N.E. 1/4 NW 1/4 Sec. 25 T. 19 N/S R. 19 E. Washoe County  
PERMIT NO.

3.	TYPE OF WORK		4.	PROPOSED USE			5. TYPE WELL
	New Well <input checked="" type="checkbox"/>	Recondition <input type="checkbox"/>		Domestic <input type="checkbox"/>	Irrigation <input type="checkbox"/>	Test <input type="checkbox"/>	
Deepen <input type="checkbox"/>	Other <input type="checkbox"/>	Municipal <input checked="" type="checkbox"/>	Geothermal <input type="checkbox"/>	Stock <input type="checkbox"/>	Other <input type="checkbox"/>		

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Concrete		0	1	1
Sand & cobbles		1	16	15
lightly cemented sand & medium		16	58	42
Volcanic sand & gravel		58	90	32
Fine & medium sands		90	170	80
Fine to Medium Sands w/ embedded clays blue & green		170	320	150
Medium sands - less clay than above				
Coarse sand & minor clay		375	445	70
Sand & minor clay		445	920	25
Compact clay		970	980	10
T.D. 480				

Date started 5-18, 1981  
Date completed 6-2, 1981

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
<u>Blew well at 750 CFM - 175 # for 5/2 hours to clean &amp; develop</u>			

BAILER TEST

G.P.M. Draw down.....feet .....hours  
G.P.M. Draw down.....feet .....hours  
G.P.M. Draw down.....feet .....hours

8.17" - 10' WELL CONSTRUCTION  
13 3/4' - 120' 9 7/8 inches Total depth 480 feet  
Diameter hole.....  
Casing record.....  
Weight per foot..... Thickness.....  

Diameter	From	To
16"	0	8
10 3/4	0	1.15
8 5/8	90	470
.....	.....	.....
.....	.....	.....
.....	.....	.....
.....	.....	.....

Surface seal: Yes  No  Type Cement Slurry  
Depth of seal..... feet

Gravel packed: Yes  No   
Gravel packed from..... feet to..... feet

Perforations:

Type perforation Jalison Screen  
Size perforation .030  

From.....	460	feet to.....	360
From.....	.....	feet to.....	.....
From.....	.....	feet to.....	.....
From.....	.....	feet to.....	.....
From.....	.....	feet to.....	.....

9. WATER LEVEL  
Static water level 18.35 Feet below land surface.....  
Flow..... G.P.M.  
Water temperature 73 ° F. Quality Good

10. DRILLERS CERTIFICATION


This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Aqua Drilling  
Address 2255 Glendale Ave Sparks

Nevada contractor's license number 15291

Nevada driller's license number 1132

Signed R. M. Hines  
Date 6-4-81



APPENDIX C

TEST PUMPING DATA



**WILLIAM E. NORK, Inc.**

Data for Well 81-195

Page 1 of 5

Distance,  $r$ , to pumping well ft.

Date 6/9-10/81

(830-0030)

Pumping well Moana Pool Geothermal Other observation wells

Location SW Reno Moana Pool

Observers DLC

## 4 Step - Drawdown Test

	DATE	time in hours	ratio $t/t'$	time, $t'$ , since pump stopped--mins.	time, $t$ , since pump started--mins.	WATER residual DD, $s' -- ft.$	drawdown, $s -- ft.$	depth -- ft.	distance to well ( $r$ ) $2 -- ft^2$	$r^2/t -- ft^2/min$	PUMPING	temp. -- °C	REMARKS
											flow -- GPM		
6-9-81	830	0				20.06					100		level of PVC pipe
	831	1				32.44	12.38					50.0	above ground
	833	3				35.39	15.33					50.5	ground = 2.26'
	835	5				37.21	17.15						
	837	7				37.76	17.70						
	840	10				38.63	18.57						
	843	13				38.96	18.90						
	846	16				39.30	19.24					51.0	
	850	20				39.51	19.45						
	855	25				39.78	19.72					51.5	
	900	30				39.88	19.82						
	905	35				40.23	20.17						
	910	40				40.49	20.43					51.5	
	920	50				40.67	20.61						
	930	60				40.95	20.89					51.5	
	950	80				41.03	20.97						
	1010	100				41.29	21.23					51.5	
	1030	120				41.65	21.59					52.0	
	1100	150				41.65	21.59						
	1130	180				41.98	21.92					51.5	
	1200	210				42.33	22.27						
	1230	240				42.44	22.38					52.0	
													Ave. T = 51.3
													C <sub>S</sub> = 4.41

Data for Well 81-195

Page 2 of 5

Distance,  $r$ , to pumping well ft.

Date 6/9/81

(830-0030 HRS.)

Pumping well Moana Pool Geothermal Other observation wells

Location SW Reno Moana Pool

Observers DLC

## 4 Step-Drawdown Test

	DATE	time in hours	ratio $t/t'$	time, $t'$ , since pump stopped--mins.	WATER residual DD, $s'$ -- ft.	drawdown, $s$ -- ft.	depth -- ft.	distance to well ( $r$ ) 2 -- ft 2	PUMPING motor - RPM	$r^2/t$ -- ft <sup>2</sup> /min	temp. -- °C	REMARKS
6-9-81	1231	241			50.76	30.70				150		
	1233	3			52.83	30.77					51.5	
	1235	5			53.82	33.76					51.5	
	1237	7			54.28	34.22						
	1240	10			54.53	34.47					51.5	
	1243	13			54.77	34.71						
	1246	16			54.95	34.89						
	1250	20			55.00	34.94					51.5	
	1255	25			55.04	34.98						
	1300	30			55.16	35.10						
	1305	35			55.76	35.70					51.5	slightly adjusted
	1310	40			55.94	35.88						
	1320	50			56.10	36.04					51.5	pump up
	1330	60			56.30	36.24						
	1350	80			56.56	36.50					51.75	slightly adjusted
	1410	100			57.07	37.01						
	1430	120			57.31	37.25						pump
	1500	150			57.31	37.25					51.75	higher
	1530	180			57.53	37.47						
	1600	210			57.61	37.55					51.75	Ave T = 51.6
	1630	240			57.86	37.80					51.75	Cs = 3.97

Data for Well 81-195.

Page 3 of 5

Distance, r, to pumping well ft.

Date 6/9-10/81

Pumping well Moana Pool Geothermal observation wells

Location SW Reno Moana Pool

Observers D.L.C./S.P.

Step drawdown

DATE	time in hours	ratio $t/t'$	WATER residual DD, s' -- ft.	drawdown, s -- ft.	depth -- ft.	distance to well ( $r$ ) <sup>2</sup> -- $\frac{ft^2}{min}$	PUMPING		REMARKS
							motor - RPM	flow -- GPM	
6-9-81	1631	481			66.05	45.99		200	51.5
	1633	483			67.85	47.79			
	1635	485			68.61	48.55			
	1637	487			69.11	49.05			51.5
	1640	490			69.44	49.38			adj back pressure up slightly
	1643	493			71.43	51.37			51.5
	1646	496			71.88	51.82			readjusted down
	1650	500			71.71	51.65			51.75
	1655	505			71.90	51.84			
	1700	510			72.06	52.00			51.75
	1705	515			72.19	52.13			
	1710	520			72.80	52.74			51.5 increased back pres.
	1720	530			73.29	53.23			now slightly
	1730	540			73.40	53.34			51.5 pressure constant
	1750	560			73.49	53.43			
	1810	580			73.30	53.24			
	1830	600			73.79	53.73			
	1900	630			74.34	54.28			
	1930	660			74.32	54.26			Ave T = 51.6
	2000	690			74.34	54.28			
	2030	720			74.36	54.30			51.5 C = 3.68

Data for Well 81-195

Page 4 of 5

Distance,  $r$ , to pumping well ft.

Date 6/10/81

Pumping well Moana Pool Geothermal Other observation wells

Location SW Reno Moana Pool

Observers DLC / SP

## Slope - drawdown

DATE	time in hours	ratio $t/t'$	time, $t'$ , since pump stopped--mins.	time, $t$ , since pump started--mins.	WATER	residual DD, $s'$ -- ft.	drawdown, $s$ -- ft.	depth -- ft.	distance to well ( $r$ ) <sup>2</sup> -- $ft^2$	$\frac{r^2/t}{ft^2/min}$	PUMPING	temp. -- °C	REMARKS
											flow -- GPM		
											motor - RPM		
2031	1721				77.31	57.25					250		
2033	3723				78.72	58.66						gate valve wide open pressure dropped to	
2035	5725				79.15	59.09						51.5	
2037	7727				79.47	59.41						240 gpm	
2040	10730				80.21	60.15						at 2046 hrs	
2043	13733				79.25	59.19							
2046	16736				79.06	59.00						well may be developed	
2050	20740				78.73	58.57							
2055	25745				79.38	59.32							
2100	30750				79.01	58.75							
2105	35755				78.12	58.06							
2110	40760				78.01	57.95							
2120	50770				77.98	57.32							
2130	60780				77.64	57.58						changed probe - scale	
2150	80800				75.55	55.50							
2210	100820				73.81	53.75						51.5 reading	
2230	120840				73.82	53.76							
2300	150870				73.64	53.58						51.5	
2330	180900				73.11	53.06							
2400	210930				73.05	52.99						51.5 pH = 7.61	
6-10-81	0030960				73.30	53.24						sp. cond = 650 mg/l	
													°C
													Ave T = 51.5
													C <sub>s</sub> = 3.99

Data for Well 81-195

Page 5 of 5

Distance,  $r$ , to pumping well ft.

Date 6/10/81

Pumping well Moana Pool Geothermal Other observation wells

Location SW Reno Moana Pool

Observers DLC / SP

	DATE	Step-drawdown Recovery			REMARKS
		temp. --- ° C	flow -- GPM	PUMPING	
6-10-81	0030	960	0	73.30	53.24
	0031	961	1	961.0	
	0032	962	2	481.0 34.50	14.44
	0035	965	5	193.0 33.41	13.35
	0037	967	7	138.1 30.62	10.56
	0040	970	10	97.0 27.90	7.84
	0043	973	13	74.8 27.85	7.79
	0046	976	16	61.0 27.44	7.38
	0050	980	20	49.0 27.01	6.95
	0055	985	25	39.4 26.98	6.92
	0100	990	30	33.0 26.41	6.35
	0105	995	35	28.4 26.00	5.94
	0110	1000	40	25.0 25.85	5.79
	0120	1010	50	20.2 25.00	4.94
	0130	1020	60	17.0 24.61	4.55
	0150	1040	80	13.0 24.04	3.98
	0210	1060	100	10.6 23.98	3.92
	0230	1080	120	9.0 23.46	3.40
	0300	1110	150	7.4 23.00	2.94
	0330	1140	180	6.3 22.99	2.93
	0715	1185	225	5.3 22.44	2.38
	1155	1645	685	2.4 22.07	2.01
	1605	1925	965	2.0 21.88	1.82
					92%
					recovery

Data for Well 81-195

Page 1 of 4

Distance,  $r$ , to pumping well ft.Date 6/10-11/81  
(2000 - 2000 hrs.)

Pumping well Moana Pool Geothermal Other observation wells

Location SW Reno Moana Pool

Observers S.P.

## Constant Discharge Test

				temp. -- °C	REMARKS
			PUMPING		
			flow -- GPM		
			motor -- RPM		
			$r^2/t$ -- ft <sup>2</sup> /min		
			distance to well ( $r$ ) <sup>2</sup> -- ft <sup>2</sup>		
			residual DD, $s'$ -- ft.		
			drawdown, $s$ -- ft.		
			depth -- ft.		
			WATER		
			ratio $t/t'$		
			time, $t'$ , since pump stopped--mins.		
			time, $t$ , since pump started--mins.		
			time in hours		
			DATE		
6-10-81	2000	0	21.74	200	
	2001	1	55.37 33.63		
	2003	3	59.35 37.61	50.0	
	2005	5	60.97 39.23	50.0	adj first q
	2007	7	61.51 39.77	51.0	
	2010	10	62.06 40.32		
	2013	13	62.07 40.33	51.0	
	2016	16	63.98 42.24		
	2020	20	64.93 43.19	51.0	
	2025	25	64.71 42.97		
	2030	30	65.65 43.91		
	2035	35	65.82 44.08		
	2040	40	65.95 44.21		
	2050	50	65.80 44.06	51.0	
	2100	60	66.36 44.62		
	2120	80	66.87 45.13		
	2140	100	66.86 45.12		
	2200	120	66.70 44.96		
	2230	150	66.83 45.09	51.5	
	2300	180	67.21 45.47		
	2330	210	67.53 45.79		
	2400	240	67.59 45.85	51.5	
6-11-81	0030	270	67.59 45.85		
	0100	300	67.60 45.86		Cond = 750 $\frac{g}{L}$
	0200	360	67.58 45.84		pH = 7.74
	0300	420	67.56 45.82	51.5	
	0400	480	67.57 45.83		

Data for Well 81-195

Page 2 of 4

Distance, r, to pumping well ft.

Date 6/10/81

Pumping well Moana Pool Geothermal Other observation wells

Location SW Reno Moana Pool

Observers S.P., D.L.C.

## Constant Discharge Test

	DATE	time in hours	WATER		PUMPING	REMARKS
			residual DD, s' -- ft.	drawdown, s -- ft.		
6-11-81	0500	540	67.51	45.77		
	0600	600	67.46	45.72		
	0700	660	67.65	45.91		Ph = 7.65
	0800	720	67.73	45.99		51.0 Cond = 700 ppm
	0900	780	67.60	45.86		
	1000	840	67.63	45.89		
	1100	900	68.03	46.29		
	1200	960	67.97	46.23		Ph meter
	1300	1020	68.24	46.50		Touchy
	1400	1080	68.33	46.59		51.0 Ph = 7.71
	1500	1140	68.28	46.54		Cond = 575 ppm
	1600	1200	68.20	46.46		
	1700	1260	68.46	46.72		
	1800	1320	68.50	46.76		Ph = 7.76
	1900	1380	68.50	46.76		51.0 Cond = 625 ppm
	2000	1440	68.48	46.74		Ph meter slowing calibrating
						$C_S = \frac{300}{46.76} = 4.28$

Data for Well 81-195

Page 3 of 4

Distance,  $r$ , to pumping well ft.

Date 6/11/81

Pumping well Moana Pool Geothermal Other observation wells

(down)

Location SW Reme, Moana Pool

Observers S.P., D.L.C.

## Constant Discharge Test Recovery

DATE	TIME	PUMPING motor - RPM	$r^2/t$ -- $\text{ft}^2/\text{min}$	distance to well ( $r$ ) $\text{ft}^2$	REMARKS
6/11-81	2000	1440	0	68.48	
	2001	1441	1	1441.0 36.05	
	2003	1443	3	481.0 31.27	
	2005	1445	5	289.0 29.29	
	2007	1447	7	206.7 28.23	
	2010	1450	10	145.0 27.66	
	2013	1453	13	111.8 27.11	
	2016	1456	16	91.0 26.85	
	2020	1460	20	73.0 26.52	
	2025	1465	25	58.6 26.25	
	2030	1470	30	49.0 26.07	
	2035	1475	35	42.1 25.81	
	2040	1480	40	37.0 25.67	
	2050	1490	50	29.8 25.36	
	2100	1500	60	25.0 25.12	
	2120	1520	80	19.0 24.66	
	2140	1540	100	15.4 24.42	
	2200	1560	120	13.0 24.27	
	2230	1590	150	10.6 24.00	
	2300	1620	180	9.0 23.85	
	2330	1650	210	7.9 23.70	
	2400	1680	240	7.0 23.65	
6/12-81	0030	1710	270	6.3 23.61	
	0100	1740	300	5.8 23.52	
	0200	1800	360	5.0 23.46	



