

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Audio-magnetotelluric Data Log and station
location map for the Dixie Valley Known
Geothermal Resource Area (KGRA) Nevada

By

R. M. Senterfit, Donald Hoover and
Charles Tippens

Open-File Report 76-292
1976

This report is preliminary and has not been
edited or reviewed for conformity with U.S.
Geological Survey standards and nomenclature.

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
1NS	pa	13.2	6.1	24.3	14.9	13.8	1.4	-	-	12.0	9.1	20.7	-
	N	8	5	13	13	10	6	-	-	5	10	1	-
	Er	2.3	0.8	1.5	0.9	1.4	0.1	-	-	1.5	0.4	-	-
1EW	pa	17.2	18.2	16.6	15.5	13.8	4.6	-	-	2.7	2.0	3.3	-
	N	11	8	7	14	10	2	-	-	4	6	1	-
	Er	2.9	2.1	1.7	1.4	0.9	.09	-	-	0.1	.09	-	-
2NS	pa	10.2	11.6	15.8	13.7	15.4	15.2	-	-	-	3.0	0.2	-
	N	5	4	6	8	7	8	-	-	-	6	1	-
	Er	1.6	1.6	2.1	.58	3.6	1.3	-	-	-	0.2	-	-
2EW	pa	15.3	21.6	13.6	17.0	17.9	18.2	-	-	-	14.6	18.5	-
	N	10	7	9	7	6	7	-	-	-	8	1	-
	Er	1.8	6.8	1.9	0.5	1.7	1.8	-	-	-	0.7	-	-
3NS	pa	16.2	7.6	13.0	16.6	15.9	13.6	-	-	-	9.2	13.6	-
	N	3	3	6	8	6	7	-	-	-	7	3	-
	Er	7.2	2.4	1.7	1.7	1.1	1.9	-	-	-	0.6	3.1	-
3EW	pa	10.6	8.8	9.2	17.7	14.2	16.9	-	-	-	6.9	15.3	-
	N	7	7	7	7	10	8	-	-	-	7	3	-
	Er	1.9	1.6	1.3	3.4	1.2	1.8	-	-	-	.98	.47	-
4NS	pa	9.8	11.4	12.2	12.4	16.0	13.1	-	-	-	9.1	4.5	-
	N	6	3	13	11	12	8	-	-	-	9	6	-
	Er	1.9	4.2	0.9	0.9	0.9	0.8	-	-	-	0.4	0.4	-
4EW	pa	11.6	8.8	7.6	10.8	10.7	10.2	-	-	-	8.6	18.5	-
	N	10	8	9	13	10	5	-	-	-	8	1	-
	Er	1.8	1.3	0.9	1.5	0.3	1.4	-	-	-	0.6	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
5NS	pa	4.9	17.1	13.0	11.2	12.3	10.4	2.1	.24	1.6	0.9	.99	-
	N	3	2	8	6	6	7	3	4	8	8	1	-
	Er	0.9	6.0	2.2	0.4	.99	1.3	0.6	.07	.24	.06	-	-
5EW	pa	11.2	13.4	12.2	10.7	11.0	13.2	4.3	1.3	2.8	2.9	9.4	-
	N	4	6	7	7	7	9	6	3	2	8	1	-
	Er	1.1	2.9	2.1	1.9	0.9	.51	.90	.27	.79	.22	-	-
6NS	pa	16.2	10.2	14.0	12.2	13.7	13.6	2.2	-	7.6	4.5	20.0	-
	N	8	8	9	10	12	10	3	-	3	10	3	-
	Er	1.1	1.4	1.2	0.6	0.4	0.8	0.4	-	0.5	0.5	2.5	-
6EW	pa	16.9	8.9	10.6	8.6	9.8	16.7	2.9	-	1.7	3.2	13.5	-
	N	8	10	11	10	10	7	3	-	4	7	1	-
	Er	1.5	1.2	0.8	0.7	0.4	2.1	0.9	-	0.1	0.4	-	-
7NS	pa	9.9	9.1	13.1	16.1	17.2	12.7	2.4	3.7	12.0	8.9	13.4	-
	N	7	7	7	15	9	13	3	2	9	6	1	-
	Er	1.7	1.4	1.1	0.8	0.4	1.1	0.6	1.4	0.6	0.6	-	-
7EW	pa	11.7	7.7	10.9	12.8	14.2	13.0	1.2	5.2	1.9	2.4	4.1	-
	N	8	11	12	10	9	8	1	3	7	9	1	-
	Er	0.6	0.7	0.6	2.6	0.9	0.9	-	1.1	0.3	0.1	-	-
8NS	pa	5.9	4.9	8.3	9.4	13.7	6.6	-	-	-	14.6	28.1	-
	N	6	6	4	6	7	6	-	-	-	7	1	-
	Er	1.2	0.8	0.3	0.4	0.6	0.8	-	-	-	0.6	-	-
8EW	pa	5.2	5.5	6.9	10.0	12.3	13.2	-	-	-	6.0	18.0	-
	N	9	6	6	6	8	6	-	-	-	7	1	-
	Er	0.9	0.4	1.7	0.8	2.2	2.9	-	-	-	0.6	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

ρ_a = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
9NS	ρ_a	16.1	7.7	2.3	6.8	5.7	13.4	-	-	-	5.6	20.5	-
	N	7	6	3	7	8	5	-	-	-	6	1	-
	Er	2.6	1.8	0.5	0.7	1.1	2.0	-	-	-	0.9	-	-
9EW	ρ_a	17.2	4.2	3.2	4.8	5.4	9.5	-	-	-	1.1	6.5	-
	N	6	6	6	6	6	7	-	-	-	7	1	-
	Er	3.6	0.8	0.5	0.4	0.3	1.0	-	-	-	0.1	-	-
10NS	ρ_a	9.2	12.1	17.3	24.1	68.3	36.1	-	-	-	1.8	6.4	-
	N	7	1	6	5	5	8	-	-	-	6	1	-
	Er	2.0	-	4.7	3.2	15.7	9.5	-	-	-	.06	-	-
10EW	ρ_a	17.3	17.7	16.7	22.9	20.2	34.0	-	-	-	8.3	11.8	-
	N	9	6	6	6	7	6	-	-	-	8	1	-
	Er	2.3	4.1	1.7	2.4	1.8	4.8	-	-	-	0.8	-	-
11NS	ρ_a	3.7	13.9	8.9	18.9	24.5	35.2	-	-	-	0.6	-	-
	N	4	5	6	8	9	8	-	-	-	7	3	-
	Er	0.7	3.1	2.3	1.8	3.1	5.4	-	-	-	.04	.02	-
11EW	ρ_a	5.6	11.4	22.5	18.7	14.7	41.3	-	-	-	11.2	30.2	-
	N	10	8	10	8	9	6	-	-	-	8	1	-
	Er	0.8	1.3	2.8	3.9	2.6	9.2	-	-	-	0.8	-	-
12NS	ρ_a	5.3	5.7	2.3	7.0	13.0	9.3	-	-	-	1.2	2.7	-
	N	8	8	7	9	13	11	-	-	-	9	1	-
	Er	0.8	0.7	0.2	0.8	0.9	1.6	-	-	-	0.1	-	-
12EW	ρ_a	3.9	3.2	3.9	4.4	5.1	4.0	-	-	-	0.6	2.7	-
	N	11	9	11	13	12	12	-	-	-	5	1	-
	Er	0.3	0.3	0.3	0.3	0.3	0.3	-	-	-	.04	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
13NS	pa	27.6	30.0	39.9	50.9	23.4	5.3	-	-	-	1.8	0.2	-
	N	6	6	6	6	6	8	-	-	-	7	1	-
	Er	3.9	6.2	7.6	2.2	1.2	1.5	-	-	-	0.1	-	-
13EW	pa	10.3	16.8	10.3	12.4	10.0	12.0	-	-	-	.06	0.1	-
	N	7	5	8	8	8	8	-	-	-	7	1	-
	Er	1.7	3.0	1.4	1.0	0.8	1.4	-	-	-	.01	-	-
14NS	pa	5.3	6.3	8.4	11.3	10.4	-	-	-	-	5.5	17.8	-
	N	11	6	11	9	14	-	-	-	-	7	1	-
	Er	0.9	1.1	0.6	0.2	0.5	-	-	-	-	0.6	-	-
14EW	pa	9.5	7.9	9.1	9.7	7.0	9.2	-	-	-	1.0	4.6	-
	N	3	9	12	9	10	6	-	-	-	9	1	-
	Er	1.8	0.6	0.6	0.9	0.5	0.2	-	-	-	.06	-	-
15NS	pa	10.5	11.2	10.3	22.4	22.4	-	-	-	-	2.4	6.6	-
	N	6	5	6	6	6	-	-	-	-	4	1	-
	Er	2.4	3.7	0.9	7.1	4.7	-	-	-	-	0.3	-	-
15EW	pa	57.4	30.9	58.2	64.0	57.0	47.9	-	-	-	0.2	1.1	-
	N	6	6	6	7	7	5	-	-	-	5	1	-
	Er	8.4	2.8	16.9	2.9	5.9	4.7	-	-	-	.02	-	-
16NS	pa	12.9	6.1	14.9	12.5	22.2	9.6	-	-	-	0.2	1.1	-
	N	9	3	5	11	11	10	-	-	-	3	1	-
	Er	1.4	1.5	1.8	0.8	1.2	0.6	-	-	-	.01	-	-
16EW	pa	23.7	15.9	19.6	15.4	16.6	12.3	-	-	-	0.3	0.5	-
	N	9	10	11	10	9	6	-	-	-	8	1	-
	Er	1.9	1.4	2.6	1.4	0.9	0.8	-	-	-	.04	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
17NS	pa	10.2	9.8	9.9	23.5	17.7	9.3	-	-	-	11.5	5.5	-
	N	3	4	6	6	8	7	-	-	-	7	1	-
	Er	2.6	2.3	1.3	3.7	1.2	0.9	-	-	-	.43	-	-
17EW	pa	17.8	12.1	12.2	13.7	10.9	4.5	-	-	-	1.1	3.4	-
	N	7	6	9	9	8	6	-	-	-	6	1	-
	Er	2.5	2.8	1.1	1.2	0.8	0.7	-	-	-	.08	-	-
18NS	pa	7.9	9.2	13.4	15.9	19.7	7.7	-	-	-	1.9	18.6	-
	N	7	11	10	13	13	8	-	-	-	5	1	-
	Er	1.6	1.2	1.5	0.6	0.4	0.8	-	-	-	0.2	-	-
18EW	pa	8.9	-	10.3	12.8	15.3	12.4	-	-	-	0.5	2.7	-
	N	13	-	8	13	14	10	-	-	-	11	1	-
	Er	0.6	-	1.0	0.8	0.4	0.8	-	-	-	.02	-	-
19NS	pa	10.9	-	6.3	7.6	8.7	4.6	-	-	-	0.2	1.3	-
	N	4	-	4	6	7	6	-	-	-	6	1	-
	Er	3.2	-	0.8	1.2	0.5	1.3	-	-	-	.01	-	-
19EW	pa	11.9	-	10.4	7.5	8.4	7.6	-	-	-	0.7	7.5	-
	N	8	-	6	6	6	6	-	-	-	6	1	-
	Er	2.5	-	2.0	1.1	1.3	1.0	-	-	-	.04	-	-
20NS	pa	4.9	6.3	7.2	9.0	9.2	3.3	-	-	-	0.1	0.3	-
	N	11	11	15	10	14	6	-	-	-	15	1	-
	Er	0.6	0.6	0.6	0.9	0.3	0.2	-	-	-	0	-	-
20EW	pa	4.0	4.8	5.5	6.3	6.5	14.2	-	-	-	1.7	6.3	-
	N	15	10	11	9	12	6	-	-	-	8	1	-
	Er	0.3	0.6	0.6	0.3	0.3	2.2	-	-	-	.03	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

 ρ_a = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
21NS	ρ_a	11.2	8.2	7.0	9.5	9.1	7.4	-	-	-	0.5	4.0	-
	N	4	5	6	6	6	5	-	-	-	4	1	-
	Er	3.1	2.5	1.3	1.3	1.2	1.2	-	-	-	0.2	-	-
21EW	ρ_a	9.3	6.4	3.7	4.7	6.2	15.4	-	-	-	0.2	1.6	-
	N	1	2	5	5	7	6	-	-	-	4	1	-
	Er	1.4	2.3	0.3	0.6	1.0	2.9	-	-	-	.03	-	-
22NS	ρ_a	3.9	4.9	8.7	9.8	9.3	7.2	-	-	-	17.6	4.0	-
	N	6	3	6	7	7	6	-	-	-	5	1	-
	Er	1.0	0.8	1.1	1.1	0.6	1.4	-	-	-	0.7	-	-
22EW	ρ_a	7.7	8.2	5.4	5.6	5.1	9.5	-	-	-	0.7	2.3	-
	N	6	5	7	7	8	2	-	-	-	8	1	-
	Er	1.8	0.5	0.6	0.6	0.3	1.1	-	-	-	.06	-	-
23NS	ρ_a	8.7	9.8	25.8	25.8	21.7	19.9	-	-	-	9.7	80.1	-
	N	4	4	9	7	7	7	-	-	-	7	1	-
	Er	1.7	1.6	4.4	5.1	3.5	1.6	-	-	-	0.7	-	-
23EW	ρ_a	14.7	17.4	12.8	17.5	27.1	15.1	-	-	-	5.0	10.3	-
	N	7	9	9	7	8	7	-	-	-	7	1	-
	Er	2.3	2.9	1.6	1.6	6.7	2.0	-	-	-	1.1	-	-
24NS	ρ_a	6.7	10.0	9.7	12.3	14.8	7.3	-	-	-	0.4	1.8	-
	N	7	3	6	6	8	6	-	-	-	7	1	-
	Er	2.7	3.1	0.9	0.6	0.9	0.8	-	-	-	.01	-	-
24EW	ρ_a	19.7	18.1	14.9	13.6	8.3	9.4	-	-	-	0.5	0.1	-
	N	7	3	5	7	4	7	-	-	-	5	1	-
	Er	1.8	5.4	3.1	1.5	0.5	1.0	-	-	-	.04	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
25NS	pa	7.4	4.1	7.3	10.1	13.7	9.6	-	-	-	0.3	3.2	-
	N	4	7	5	6	6	4	-	-	-	5	1	-
	Er	1.8	0.4	0.9	0.9	1.7	1.4	-	-	-	.03	-	-
25EW	pa	8.1	6.9	7.0	7.7	8.5	-	-	-	-	0.1	0.5	-
	N	7	4	4	5	5	-	-	-	-	3	1	-
	Er	0.6	1.0	1.4	1.3	0.7	-	-	-	-	0.02	-	-
26NS	pa	46.8	54.4	53.8	54.4	68.4	71.1	-	-	-	18.7	55.4	-
	N	8	7	6	8	7	7	-	-	-	8	1	-
	Er	7.1	7.4	6.2	2.9	4.7	5.4	-	-	-	1.5	-	-
26EW	pa	53.2	33.2	46.3	53.7	54.3	65.4	-	-	-	2.3	3.2	-
	N	5	8	6	6	7	5	-	-	-	5	1	-
	Er	9.7	5.4	6.2	10.2	7.2	7.6	-	-	-	0.6	-	-
27NS	pa	4.7	5.7	6.9	10.4	8.4	8.3	-	-	-	9.2	8.8	-
	N	5	5	7	6	5	6	-	-	-	7	1	-
	Er	0.9	1.6	0.6	1.2	2.9	0.3	-	-	-	1.2	-	-
27EW	pa	7.5	7.5	6.4	6.7	7.5	6.6	-	-	-	0.9	8.9	-
	N	4	5	7	6	6	6	-	-	-	7	1	-
	Er	0.4	1.3	0.6	0.4	0.8	0.7	-	-	-	0.1	-	-
28NS	pa	8.7	5.4	7.6	7.5	8.2	5.8	-	-	-	5.7	10.4	-
	N	6	4	6	6	6	6	-	-	-	5	1	-
	Er	1.9	1.6	0.6	0.8	1.2	0.5	-	-	-	0.1	-	-
28EW	pa	8.1	11.9	7.0	7.6	8.0	7.6	-	-	-	1.3	11.3	-
	N	8	3	4	6	6	6	-	-	-	8	1	-
	Er	1.4	0.9	1.4	1.0	0.5	0.5	-	-	-	0.2	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
29NS	pa	11.2	10.8	6.7	6.7	7.7	6.1	-	-	-	18.6	6.9	-
	N	1	3	3	6	7	5	-	-	-	4	1	-
	Er	-	1.7	1.6	1.1	0.5	1.5	-	-	-	2.2	-	-
29EW	pa	14.4	5.4	8.3	4.5	7.2	9.6	-	-	-	1.3	1.0	-
	N	3	3	6	6	6	3	-	-	-	6	1	-
	Er	0.3	1.3	1.7	0.4	0.3	0.9	-	-	-	0.3	-	-
30NS	pa	13.0	9.2	14.6	10.2	9.9	10.9	-	-	-	12.5	11.4	-
	N	8	5	6	7	8	3	-	-	-	5	1	-
	Er	2.3	2.2	1.2	0.4	0.4	5.3	-	-	-	1.6	-	-
30EW	pa	12.2	13.0	15.2	9.5	8.3	14.4	-	-	-	3.4	18.8	-
	N	7	4	9	7	7	3	-	-	-	3	1	-
	Er	0.9	1.0	1.1	0.6	0.5	1.9	-	-	-	0.5	-	-
31NS	pa	2.8	3.2	3.1	3.3	4.0	3.2	-	-	-	19.4	9.3	-
	N	3	4	8	8	5	4	-	-	-	3	1	-
	Er	0.4	0.2	0.6	0.2	0.2	0.3	-	-	-	0.3	-	-
31EW	pa	3.5	3.2	4.4	4.1	4.3	15.3	-	-	-	-	6.9	-
	N	3	3	8	8	6	1	-	-	-	-	1	-
	Er	0.3	0.7	0.4	0.8	0.2	-	-	-	-	-	-	-
32NS	pa	6.7	9.4	9.9	7.8	16.1	11.2	-	-	-	2.2	12.2	-
	N	4	6	6	6	7	6	-	-	-	8	1	-
	Er	2.6	0.9	1.5	1.9	0.6	1.2	-	-	-	0.2	-	-
32EW	pa	6.0	5.8	6.2	5.7	10.8	9.8	-	-	-	1.8	6.9	-
	N	9	7	7	6	8	5	-	-	-	8	1	-
	Er	0.7	0.6	1.0	0.4	2.6	0.6	-	-	-	0.2	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
33NS	pa	4.5	7.6	4.4	4.6	4.5	2.2	-	-	-	2.1	2.7	-
	N	7	3	6	10	9	4	-	-	-	6	1	-
	Er	0.5	1.3	0.6	0.5	0.3	0.4	-	-	-	0.1	-	-
33EW	pa	5.2	3.0	4.2	4.1	3.0	3.0	-	-	-	0.7	1.9	-
	N	11	5	10	10	10	4	-	-	-	4	1	-
	Er	0.4	0.4	0.4	0.2	0.1	0.3	-	-	-	0.1	-	-
34NS	pa	4.9	6.1	9.8	8.8	16.0	8.7	-	-	-	6.5	92.0	-
	N	5	6	7	7	8	3	-	-	-	2	1	-
	Er	0.2	1.1	1.5	0.6	0.7	0.5	-	-	-	0.8	-	-
34EW	pa	9.8	6.3	10.3	8.2	8.9	10.0	-	-	-	5.1	24.0	-
	N	9	7	8	7	6	3	-	-	-	4	1	-
	Er	0.9	0.8	0.5	0.6	0.8	0.6	-	-	-	0.7	-	-
35NS	pa	9.4	6.5	14.6	11.0	21.6	12.5	-	-	-	52.0	17.1	-
	N	1	2	5	10	8	2	-	-	-	4	1	-
	Er	-	0.3	3.1	0.7	1.2	0.7	-	-	-	8.4	-	-
35EW	pa	13.0	12.9	11.2	11.7	15.2	22.6	-	-	-	9.2	24.4	-
	N	10	4	15	9	5	5	-	-	-	5	1	-
	Er	0.9	1.4	0.7	0.7	0.9	7.0	-	-	-	0.3	-	-
36NS	pa	12.2	10.3	16.0	24.5	21.0	14.4	-	-	-	25.4	16.9	-
	N	3	4	6	9	7	4	-	-	-	5	1	-
	Er	0.7	1.9	2.2	2.3	0.7	3.3	-	-	-	0.5	-	-
36EW	pa	10.4	11.6	11.4	14.9	11.9	11.3	-	-	-	0.4	0.9	-
	N	7	6	7	9	7	4	-	-	-	7	1	-
	Er	0.5	1.0	1.1	1.4	0.5	1.6	-	-	-	0.03	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
37NS	pa	14.0	16.8	15.1	18.3	24.5	11.1	-	-	-	22.1	8.4	-
	N	6	5	11	9	11	5	-	-	-	3	1	-
	Er	2.6	2.9	1.5	1.2	1.4	1.2	-	-	-	2.0	-	-
37EW	pa	9.0	10.0	10.5	9.9	10.7	17.7	-	-	-	1.1	5.4	-
	N	12	7	9	10	8	4	-	-	-	5	1	-
	Er	0.6	1.4	0.8	0.5	0.4	8.1	-	-	-	0.2	-	-
38NS	pa	8.6	10.3	12.3	15.7	23.4	5.4	-	-	-	9.9	18.5	-
	N	4	4	7	6	6	4	-	-	-	5	1	-
	Er	1.8	2.9	1.8	2.1	1.5	1.2	-	-	-	0.4	-	-
38EW	pa	9.3	8.8	11.5	8.3	13.0	13.2	-	-	-	2.6	10.1	-
	N	6	10	6	5	6	3	-	-	-	10	1	-
	Er	1.5	1.7	0.9	1.7	0.6	1.5	-	-	-	0.1	-	-
39NS	pa	26.5	20.3	24.9	26.3	29.3	18.3	-	-	-	8.6	34.4	-
	N	3	4	7	7	6	1	-	-	-	2	1	-
	Er	11.0	0.4	2.9	3.5	4.3	-	-	-	-	0.2	-	-
39EW	pa	34.3	28.1	32.0	23.5	17.2	-	-	-	-	1.2	3.2	-
	N	11	8	12	11	9	-	-	-	-	4	1	-
	Er	2.2	2.5	1.6	1.2	0.7	-	-	-	-	0.1	-	-
40NS	pa	22.4	29.9	27.5	32.8	37.0	24.6	-	-	-	1.7	4.1	-
	N	5	5	8	9	10	2	-	-	-	8	1	-
	Er	3.3	3.6	1.7	1.5	1.8	2.7	-	-	-	0.2	-	-
40EW	pa	48.9	44.9	46.5	63.1	86.7	87.0	-	-	-	0.8	1.0	-
	N	7	8	12	11	8	2	-	-	-	10	1	-
	Er	4.8	2.8	3.0	2.4	3.1	10	-	-	-	0.04	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

ρ_a = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
41 NS	ρ_a	22.1	12.3	16.3	26.4	34.8	22.3	-	-	-	5.1	13.4	-
	N	4	2	8	9	10	7	-	-	-	3	1	-
	Er	4.6	6.2	2.3	3.2	2.8	5.2	-	-	-	1.3	-	-
41 EW	ρ_a	55.3	30.7	31.6	23.7	30.7	24.1	-	-	-	0.7	1.8	-
	N	7	7	11	12	10	7	-	-	-	11	1	-
	Er	5.8	4.9	5.0	1.8	1.5	2.4	-	-	-	.02	-	-
	ρ_a												
	N												
	Er												
	ρ_a												
	N												
	Er												
	ρ_a												
	N												
	Er												
	ρ_a												
	N												
	Er												
	ρ_a												
	N												
	Er												